

GLOB'A



Features:

GLOB'A Is Decorative Magnetic track light installed on Low Voltage Magnetic Track.

Available in different styles and finishes to match various interior decors.

Body Material made of aluminum with LED technology for energy savings and longevity.

This is ideal for highlighting specific objects or areas.

Low-voltage DC40V input scheme is adopted.

The magnetic track allows you to easily move and adjust the position of the light fixture along the track.

Technical Specifications:

Input Voltage: 40V DC, 50 Hz.

Wattage: 10W

High Lumen: 80lm/w

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: SMD Module

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at ta 25°C

(L80/B10)

Fields of Application:

Retail

Education

Galleries hotels

Living spaces

Installation Method:

On an electrified Magnetic track 40V DC

Wattage(W)	:	10	10		
Finish	:	White(W)	Black(B)	Gray(G)	
Kelvin*	:	2700K	3000K	4000K	5000K
Beam Angle	:	135°			
CRI	:	90+			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming Bluetooth
Type	:	A	B		

*Special Color and Finish on request

Product Code (76511410'A):

Wattage	Lumens(lm)	Dimension (LxWxH) mm
10	800LM	114x100x131
10	800LM	114x100x100
		0

*Luminous lux value is calculated for 4000K CRI>90

Photometric:

Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 76511410'A 27K 135D 9 1 W A

CCT	Beam Angle	CRI	Driver	Finish	Type
27K - 2700K	135D - 135°	9->90	1 - ON/OFF	W-White	A
30K - 3000K			2 - 0/1-10V	B-Black	B
40K - 4000K			3 - DALI	G-Gray	
50K - 5000K			4 - Phase Dimming		
			5 - Bluetooth		

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C