


HAZEL



Description:

HAZEL is outdoor Wall washer is designed to provide powerful, uniform illumination. Its Die cast aluminum housing offers reliable performance in demanding outdoor environments.

The adjustable mounting bracket allows flexible positioning and precise aiming of the light beam, making it suitable for wall, ceiling, ground, and base-mounted installations.

Toughened glass surface, with high hardness, not easy to break.

Its clean, contemporary design makes it an ideal choice for illuminating facades, gardens, pathways, public spaces, and other outdoor areas.

Product Specifications:

Housing : Die cast aluminum
Coating: Powder Coating
Glass : Tempered Glass
Light Source: CREE / Osram
Gasket: Molding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Surface / Spike Mounted
Adjustable: Yes

Technical Specifications:

Wattage: 24W
Voltage: DC24V / 220-240VAC
Frequency: 50-60Hz
Lumen: 75lm/W
Mac Adam: 3 Step
Safety Class: III
Working Temperature:-40°C to 50°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	24W
Finish	:	Black (B) / Grey (G) / White (W) / Silver (S)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	50°
CRI	:	80+ 90+
Control Mode	:	ON/OFF / DALI

*Lumen values are calculated at 50° beam angle, 3000K color temperature and CRI 90.

Order Code:

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
5420093	24 - 24W	27-2700K 30-3000K 40-4000K 60-6000K	D-24VDC	50 - 50°	B- Black G - Grey W - White S - Silver	1-ON/OFF 2-DALI

Ex: Order Code: 54200932427D'50B1

Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Product Code	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
5420093	24 - 24W	27-2700K 30-3000K	A - 220 - 240VAC	50 - 50°	B- Black G - Grey	1-ON/OFF 2-DALI


Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

40-4000K
60-6000K

W - White
S - Silver

Ex: Order Code: 54200932427A'50B1

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C