
pluxb

IP66 IK08

HEDES





Description:

HEDES is a outdoor linear wall washer is lighting fixtures designed to provide uniform illumination along the length of a wall or other vertical surfaces.
No IR light source and UV-assisted technology, It also offers directional irradiation with uniform light color and high brightness.
The toughened glass surface offers high hardness and impact resistance, and the series provides various CCT options, C5 Marine Grade Coating, Honeycomb, and Anti-glare shield options, making it a versatile solution for diverse project specifications.
Customizable lengths include 250mm, 500mm, 750mm, and 1.5m.
They are commonly used in architectural lighting to enhance the aesthetics of buildings, highlight textures, and create visually appealing lighting effects.
Control Mode : DMX512

Product Specifications:

Housing : Die cast Aluminum
Glass : Tempered glass
Coating : Powder Coating
Light Source: Osram / Cree
Gasket: Molding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Surface Mounted
Adjustable : Yes

Technical Specifications:

Wattage: 12 -36W
Voltage: 24VDC / AC85V-265V
Frequency: 50-60Hz
Lumen: Single Color (3000K) - 120lm/W
RGBW (3000K) - 65lm/W
Mac Adam: 3 Step
Safety Class: III
Working Temperature:-25°C to 50°C
Life Time: 50,000hrs (L80/B10) at 25°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	12W / 26W / 36W
Finish	:	Black (B) / Grey (G)
Kelvin*	:	2700K/ 3000K/ 4000K/ 6000K / RGBW
Beam Angle	:	8°/ 15°/ 30°/ 45°/ 60°/ 15°x 45°/ 10°x 60°
CRI	:	80+
Control Mode	:	ON/OFF / DALI / DMX

*Lumen values are calculated at 45° beam angle, 4000K color temperature and CRI 80.

Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5425014	12 - 12W (250mm)	27-2700K	D-24VDC	8-8°	B - Black	1-ON/OFF
	26 - 26W (500mm)	30-3000K		15-15°	G - Grey	2-DALI
	36 - 36W (1000mm)	40-4000K		30-30°		3-DMX
		60-6000K		45-45°		
		92-RGBW		60-60°		
		93-RGBW DMX		15x45-15°x45°		
				10x60-10°x60°		








Ex: Order Code: 54250141227D'8B1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5425014	12 - 12W (250mm)	27-2700K	A - 85V-265VAC	8-8°	B - Black	1-ON/OFF
	26 - 26W (500mm)	30-3000K		15-15°	G - Grey	2-DALI
	36 - 36W (1000mm)	40-4000K		30-30°		
		60-6000K		45-45°		
				60-60°		
				15x45-15°x45°		
				10x60-10°x60°		

Ex: Order Code: 54250141227A'8B1

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C