



























Description:

JANE is a outdoor Double Emission wall lamp with special optical design like Spot + Medium Flood, Spot + Wide Flood, Double Diffused, Double Extra Wide Flood, Double Spot, Double Medium Flood and Double Wide Flood Light distuributions. The design is simple and rich in texture. it is composed of die-casting aluminum, processed by means of open pore anodizing + powder coating; the diffuser is made of extra clear glass - tempered with a silk-screening treatment.

The lamp is suitable for indoor and outdoor facade lighting architectural decorative lighting,

Product Specifications:

Housing: Die cast Aluminium Glass: Tempered Glass Diffuser: Clear Glass Net Weight: 0.32KG LED Quantity: 2 LED

Gasket: Moulding shaped silicone seal Lens/Reflector: Optical lens (efficiency>90%) Power Cable: 0.5 mt. power cable included Driver: High efficiency, low flicker driver Installation Type: Surface mounted

Adjustable: No

Technical Specifications:

Wattage: 6.5W

Voltage: 180-264VAC Frequency: 50-60Hz

Light Source: OSRAM/EPISTAR/CREE

Lumen: 150lm/W Mac Adam: 2 Step Safety Class: III

Dimension: L60xH61mm

Working Temperature: -20°C to 50°C Life Time: 50,000hrs (L80/B10) at 25°C

Warranty: 5 Years

Parameter:

Wattage(W) 6.5W

Finish : Dark Brown (DB) / Grey (G) / White (W) / Black (B)

2700K/3000K/4000K Kelvin*

36° / 60° / 96° / 110° (Asymmetrical) Beam Angle

CRI 90+

Control Mode : ON/OFF / DALI / 0 / 1-10V

Standards:

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Order Code:

F	Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5	40059	06-6.5W	27-2700K	A-180 - 264VAC	A36-Asymmetrical 36°	DB-Dark Brown	1-ON/OFF
			30-3000K		A60-Asymmetrical 60°	G-Grey	2-DALI
			40-4000K		A96 -Asymmetrical 96°	W-White	3-0/1-10V
					A110 - Asymmetrical 110°	B-Black	

5400590627A'A36DB

Ex: Order Code: 1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C