


JAS



Description:

JAS is a Linear Wall outdoor lighting fixtures designed to be installed flush with the wall surface, providing subtle and aesthetically pleasing illumination. These lights typically have a linear or elongated shape, allowing them to seamlessly blend into pathways, driveways, or other outdoor areas.

Linear Wall Lights often feature durable and weather-resistant materials to withstand outdoor conditions

It comes with different CCT LED sources, this family is a perfect solution to the requirement.

They are commonly used for accentuating architectural features, guiding pathways, or creating ambiance in outdoor spaces.

Product Specifications:

Front cover : Stainless Steel 316 SUS
Housing : Die cast Aluminium grey
Diffuser : Tempered Glass
Gasket: Moulding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Wall Recessed
Adjustable: No

Technical Specifications:

Wattage: 6 - 9W
Voltage: 220-240VAC
Frequency: 50-60Hz
Light Source: OSRAM/EPISTAR/CREE
Lumen: 100lm/W
Mac Adam: 3 Step
Safety Class: II
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:


Wattage(W)	:	6W / 9W
Finish	:	Stainless Steel 316 SUS (SS)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	8° / 15° / 25° / 45° / 60°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539195	06-6W(3X2W)	27-2700K	A-220-240VAC	8-8°	SS-Stainless Steel 316	1-ON/OFF
	09-9W(3X3W)	30-3000K		15-15°		2-DALI
		40-4000K		25-25°		3-0/1-10V
		60-6000K		45-45°		
				60-60°		

Ex: Order Code: 5391950627A8SS1

Photometric:



Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3