


## KIRA II



### Features:

KIRA II Recessed Spotlight modern designed, die cast aluminum body with solvent free power coated anodized, with High Efficiency Alanoood Reflector and PMMA Lens.  
Aluminum Body helps in dissipating heat effectively, reducing the risk of overheating and extending the lifespan of the light with PMMA lens, With different finish reflector RAL 9003 / RAL 9006 / RAL 9005 and any another special finish as your request.  
High thermal conductivity double-sided aluminum substrate.  
High light Transmissivity.  
Homogenous, well-balanced light dispersing, no shadow.

### Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.  
Wattage: 15W  
High Lumen: 100lm/w  
2STEP Mac / 3 STEP Mac Adam  
High efficiency, low flicker driver  
Lamp Type: COB  
Operating Temperature: -20°C to 45°C  
Glow Wire Test 850° C  
Warranty: 5 Years  
Life Time: 50,000hrs at 25°C (L80/B10)

### Fields of Application:

Retail  
Education  
Galleries hotels  
Living spaces  
Conference rooms  
Counters  
Restaurants

### Installation Method:

Recessed

Wattage(W)	:	15					
Finish	:	White(W)	Black(B)	Gray(G)			
Kelvin*	:	2700K	3000K	3500K	4000K	5000K	5700K
Beam Angle	:	15°	21°	31°			
CRI	:	80+	90+	97+			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth	




\*Special Color and Finish on request

### Product Code (98708215):

Wattage	Lumens(lm)	Dimension(ØxH) mm	Cut Out(Ø)
15	1500LM	81x69	75

\*Luminous øux value is calculated for 4000K CRI>80

### Photometric:



- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 98708215 27K 15D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	15D - 15°	8->80	1 - ON/OFF	W-White
30K - 3000K	21D - 21°	9->90	2 - 0/1-10V	B-Black
35K - 3500K	31D - 31°	9->97	3 - DALI	G-Gray
40K - 4000K			4 - Phase Dimming	
50K - 5000K			5 - Bluetooth	
57K - 5700K				