


KISSA



62.5

Ø113

Features:

KISSA is a recessed downlight, expertly crafted from Die Cast Aluminum, PMMA Diffuser and finished with a solvent-free powder coating to ensure long-lasting durability and resistance to wear.

It features a customized anti-glare reflector that supports multiple beam angles, achieving UGR <19 to ensure visual comfort in compliance with lighting standards.

Equipped with a 3 CCT switchable function, it provides versatile color temperature adjustment to suit different applications.

Optional aluminium Reflector Chrome, Black and White Finish.

Designed for reliable performance, stable light output, and easy installation in commercial, office, and residential environments.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50/60Hz.
 Wattage: 6-10W
 Efficiency: 140lm/W
 High efficiency, low flicker driver
 4 STEP Mac Adam
 Lamp Type: COB
 Lamp Brand : OSRAM
 Operating Temperature: -20°C to 45°C
 Glow Wire Test 850° C
 Warranty: 5 Years
 Lifetime : 100,000hrs at a 25°C (L80/B10)

Fields of Application:

Retail
 Education
 Galleries hotels
 Living spaces
 Museums
 Restaurants
 Painting Exhibitions
 Theaters

Installation Method:

Recessed

Wattage(W)	:	6	8	10
Finish	:	White(W) Black(B)		
Kelvin*	:	2700K	3000K	3500K 4000K 5700K
Beam Angle	:	90°		
CRI	:	90+		
Driver	:	ON/OFF	DALI	Phase Dimming 1-10V

*Special Color and Finish on request


Product Code (96811310):

Wattage	Lumens(lm)	Dimension (ØxH) mm	Cut Out (mm)
6	840LM	113x62.5	90-100
8	1,120LM	113x62.5	90-100
10	1,400LM	113x62.5	90-100

*Luminous flux value is calculated for 4000K CRI>90, 3 STEP Mac Adam

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96811310 27K 90D 9 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	90D - 90°	9->90	1 - ON/OFF	W-White
30K - 3000K			2 - DALI	B-Black
35K - 3500K			3 - Phase Dimming	
40K - 4000K			4 - 1-10V	
57K - 5700K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C