

KISSA



66

Ø140



Features:

KISSA is a recessed downlight, expertly crafted from premium aluminum and finished with a solvent-free powder coating to ensure long-lasting durability and resistance to wear.

It features a customized anti-glare reflector that supports multiple beam angles, achieving UGR <19 to ensure visual comfort in compliance with lighting standards.

Equipped with a 3 CCT switchable function, it provides versatile color temperature adjustment to suit different applications. Designed for reliable performance, stable light output, and easy installation in commercial, office, and residential environments.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50/60Hz.

Wattage: 15W

Efficiency: 150lm/W

High efficiency, low flicker driver

3 STEP Mac Adam

Lamp Type: COB

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Lifetime 50,000hrs at a 25°C(L90/B10)

Fields of Application:

- Retail
- Education
- Galleries hotels
- Living spaces
- Museums
- Restaurants
- Painting Exhibitions
- Theaters

Installation Method:

Recessed

Wattage(W)	:	15				
Finish	:	White(W)	Black(B)			
Kelvin*	:	2700K	3000K	3500K	4000K	5700K
Beam Angle	:	90°				
CRI	:	90+				
Driver	:	ON/OFF	DALI	Phase Dimming	1-10V	


*Special Color and Finish on request

Product Code (96814015):

Wattage	Lumens(lm)	Dimension (ØxH) mm	Cut Out (mm)
15	2200LM	140x66	125-135

*Luminous flux value is calculated for 4000K CRI>90, 3 STEP Mac Adam

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96814015 27K 90D 9 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	90D - 90°	9->90	1 - ON/OFF	W-White
30K - 3000K			2 - DALI	B-Black
35K - 3500K			3 - Phase Dimming	
40K - 4000K			4 - 1-10V	
57K - 5700K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C