
pluxb

IP65 IK08

KRAT





Description:

KRAT is modern LED bollard light combines a distinctive geometric design with reliable outdoor performance.
Constructed with a durable weather-resistant housing and rated IP65, it provides long-lasting protection against dust and water ingress.
It include features such as corrosion resistance , dustproof, anodized and polished, sand blasted, not easy to rust and fade. It comes with different CCT LED sources, finishes and C5 Marine coating, this family is a perfect solution to the requirement.
This type of fixture is often used for pathway, landscape lighting, Parking lots , Park And Garden due to its minimalist, contemporary style.
Available Height Options: 250mm, 500mm , 700mm, 1000mm.
Other heights can be customized.

Product Specifications:

Housing : Die cast Aluminium
Diffuser : Clear PMMA
Coating: Powder Coating
Light Source: Cree / Osram
Gasket: Moulding shaped silicone seal
Power Cable: 0.5 mtr. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Ground Mounted
Adjustable: No

Technical Specifications:

Wattage: 10W
Voltage: 220-240VAC
Frequency: 50-60Hz
Lumen: 75lm/W
Mac Adam: 3 Step
Safety Class: III
Working Temperature:-25°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	10W
Finish	:	RAL 9004 (B) / RAL 9006 (LG) / RAL 9007 (DG) / RAL 9016 (W)
Kelvin*	:	2700K / 3000K / 4000K / 6000K
Beam Angle	:	360°
CRI	:	80+ 90+
Control Mode	:	ON/OFF DALI

Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3


Order Code:

Product Code	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
547145	10 - 10W	27-2700K 30-3000K 40-4000K 60-6000K	A - 220 - 240VC	360 - 360°	B - RAL 9004 LG - RAL 9006 DG - RAL 7024 W - RAL 9016	1-ON/OFF 2-DALI

Ex: Order Code: 5471451027A'360B1

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C