


KYLO



∅73mm



Features:

KYLO Surface mounted Downlight, with Adjustable front lid, modern look with a minimalistic profile, allowing the light to blend seamlessly into various interior decors.

High quality of die cast aluminum body, ensuring superior durability and excellent heat dissipation.

It is easy to adjust the angle of the light to reduce glare or ensure an even spread of light in the desired direction.

The lens made of high-quality, impact-resistant materials, ensuring that it can withstand environmental conditions while still maintaining the clarity of light output.

The product has ultra UGR 20, so the light output is soft and doesn't create visual discomfort.

Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.

Wattage: 8-10W

Efficacy: 80lm/W

High efficiency, low flicker driver

3 STEP Mac Adam

Lamp Type: COB

Light source: Bridgelux

Operating Temperature: -20°C to 45°C

Glow Wire Test 850" C

Warranty: 5 Years

Life Time: 50,000hrs at 25°C (L80/B10).

Fields of Application:

- Retail
- Galleries hotels
- Living spaces
- Conference rooms
- Counters
- Restaurants

Installation Method:

Surface Mounted

Wattage(W)	:	8	10			
Finish	:	White (W)	Black(B)			
Kelvin*	:	2700K	3000K	4000K	5700K	6500K
Beam Angle	:	15°	24°	36°	60°	
CRI	:	90+				
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Casambi

*Special Color and Finish on request




Product Code (96807310):

Wattage	Lumens(lm)	Dimension(Ø x H) mm
8	640LM	73x115
10	800LM	73x115

*Luminous flux value is calculated for 4000K CRI>90, 3 STEP Mac Adam

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96807310 27K 15D 9 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	15D - 15°	9->90	1 - ON/OFF	W-White B-Black
30K - 3000K	24D - 24°		2 - 0/1-10V	
40K - 4000K	36D - 36°		3 - DALI	
57K - 5700K	60D - 60°		4 - Phase Dimming	
65K - 6500K			5 - Casambi	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C