




### LACTO





















# **Description:**

LACTO is an inground light is a durable and stylish outdoor lighting solution, crafted from high-quality die-cast aluminum with excellent corrosion resistance.

Designed to withstand harsh environmental conditions, it features a robust tempered glass cover that ensures longevity and protection.

The fixture is engineered to provide a unique lighting effect, with illumination flushing from two opposite sides, creating a sleek and modern ambiance.

The entire lamp structure is waterproof with advanced technology, offering a reliable IP67 protection grade.

Ideal for pathways, driveways, gardens, and architectural accents.

# **Product Specifications:**

Housing: Die cast aluminum grey

Coating: Powder Coating Glass: Tempered glass

Gasket: Molding shaped silicone seal

Lens/Reflector: Optical lens (efficiency>90%) Power Cable: 0.5 mt. power cable included Driver: High efficiency, low flicker driver

Installation Type: Inground

### **Technical Specifications:**

Wattage: 3W

Voltage: 85-265V AC Frequency: 50-60Hz


Light Source: OSRAM/EPISTAR/CREE

Lumen: 120lm/W Mac Adam: 3 Step Safety Class: III

Working Temperature:-40°C to 50°C Life Time: 50,000hrs (L80/B10) at 35°C

Warranty: 5 Years

#### Photometric:



# Parameter:

Wattage(W) 3W

Finish : Black (B)

2700K/3000K/4000K Kelvin\*

Beam Angle 180°

CRI 80

Control Mode ON/OFF / DALI / 0 / 1-10V

#### Standard:

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

<b>Product Code</b>	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
544204	3 - 3W	27-2700K	A - 265 - 85VAC	180 - 180°	G-Grey	1-ON/OFF
		30-3000K			B-Black	2-DALI
		40-4000K				3-0/1-10V

Ex: Order Code: 544204327A'180G1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C