



LAFA



Suitable Accessories



Features:

LAFA a modern cylindrical LED track spotlight designed for flexible lighting applications, die cast aluminum, with PMMA Optics.

The luminaire is compatible with 48V low-voltage magnetic track systems, ensuring safe, efficient, and easy installation with tool-free magnetic mounting.

In addition, the fixture can also be supplied with a standard track adapter, allowing it to be used on conventional high-voltage track systems. This dual compatibility provides maximum flexibility for different project requirements.

Flexible adjustable beam angles, with high efficiency heat dissipation.

The product also available with a range of accessories, including a honeycomb louvre for superior glare control, linear spread glass for elongated light distribution, and clear glass for maximum output and clarity. This combination of refined design, advanced optics.

Homogenous, well-balanced light dispersing, no shadow.

Technical Specifications:

Input Voltage: 48V AC, 50 Hz.

Wattage: 04W

High Lumen: 55lm/W

3 STEP Mac Adam

High efficiency, low Flicker driver

Lamp Type: SMD

Chip Brand: CREE / Bridgelux

Driver Brand: VS / OSRAM / Tridonic

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at 25°C (L85/B10).

Fields of Application:

Commercial places

Galleries hotels

Car displays

Museums

Restaurants

Clothing shops

Furniture Shops

Installation Method:

On an electrified track or special base.

Wattage(W)	:	4					
Finish	:	White(W)	Black(B)				
Kelvin*	:	2700K	3000K	3500K	4000K	5700K	6500K
Beam Angle	:	17°	26°	31°	53°		
CRI	:	80+	90+				
Driver	:	ON/OFF	0/1-10V	DALI	Casambi		


*Special Color and Finish on request

Product Code (96502504):

Wattage	Lumens(lm)	Dimension(Ø x H) mm
4	220LM	25x60

*Luminous flux value is calculated for 3000K and CRI>90, 3 STEP Mac Adam.

Photometric:



- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 96502504 27K 17D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	17D - 17°	8->80	1 - ON/OFF	W-White
30K - 3000K	26D - 26°	9->90	2 - 0/1-10V	B-Black
35K - 3500K	31D - 31°		3 - DALI	
40K - 4000K	53D - 53°		4 - Casambi	
57K - 5700K				
65K - 6500K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C