


## LILA



### Description:

LILA series of high-power LED wall washers combines sophisticated design with advanced thermal management, thereby ensuring fixture stability and prolonged operational lifespan. The fixture's housing is precision-molded from premium 6063 aluminum alloy and finished with an anodized coating, providing exceptional durability and corrosion resistance. Available in Metallic Gray (RAL9023) with a high-gloss liquid coating and high-temperature grilling, the fixture also offers a 50µm liquid coating to enhance heat dissipation and lifespan, or a 120µm RAL7011 metallic grey powder coating for robust UV protection. With THD less than 10% and a power factor greater than 0.9, it ensures high electrical efficiency and superior performance. The toughened glass surface offers high hardness and impact resistance, and the series provides various CCT options, C5 Marine Grade Coating, Honeycomb, and Anti-glare shield options, making it a versatile solution for diverse project specifications. Customizable lengths include 250mm, 500mm, 750mm, and 1.5m. These fixtures are ideally suited for accentuating architectural elements, illuminating pathways, and enhancing the ambiance of outdoor environments.

### Product Specifications:

Housing : Die cast Aluminum  
Glass : Tempered glass  
Coating : Powder Coating / Liquid Coating.  
Gasket: Molding shaped silicone seal  
Lens/Reflector : Optical lens (efficiency>90%)  
Power Cable: 0.5 mt. power cable included  
Driver : High efficiency, low flicker driver  
Installation Type: Surface Mounted  
Adjustable : Yes

### Technical Specifications:

Wattage: 12 - 48W  
Voltage: 24VDC  
Frequency: 50-60Hz  
Power Factor : >0.9  
Light Source: OSRAM/EPISTAR/CREE  
Lumen: 50lm/W  
Mac Adam: 3 Step  
Safety Class: III  
Working Temperature:-25°C to 50°C  
Life Time: 50,000hrs (L80/B10) at 25°C  
Humidity : <95%  
Warranty: 5 Years

### Standards :

EN 60598-1  
EN 60598-2-2  
EN 60598-3-2  
EN 60598-3-3

### Parameter:

Wattage(W)	:	12W / 15W / 18W / 24W / 36W / 48W
Finish	:	Black (B) / White (W)
Kelvin*	:	RGBW / RGBW DMX
Beam Angle	:	20°/ 30°/ 45°/ 60°/ 20x40°/ 18x50°
CRI	:	80+
Control Mode	:	ON/OFF / DALI / DMX

### Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5423873	12 - 12W (300mm)	82-RGBW	D - 24VDC	15-15°	B-Black	1-ON/OFF
	18 - 18W (500mm)	83-RGBW DMX		20-20°	W-White	2-DALI
	24 - 24W (500mm)			30-30°		3-DMX

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

36 - 36W (1000mm)  
48 - 48W (1000mm)

45-45°  
60-60°  
18x50-18x50°

**Ex: Order Code:** 54238731282D'15B1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C