


LINE'T 100



Bracket



Accessories :

End Cap Spring clip




Optics Diffuser :



PMMA Matt Diffuser

Prismatic Lens



Prismatic Lens + PMMA Sheet

Opal Diffuser

Features:

LINE is high quality Trimless bendable aluminum using the highest standard 6063-T6 aluminum stronger than 6063-T5, and deep anodizing (more than 12µm) of profile protects the aluminum against corrosion, extends durability.

Anodized Aluminum different options of finishes, White, Black, Silver or Graphite Grey, Solvent free power coating, or any customized color as your project requirements.

Lighting fixtures can be connected into linear and polygonal lighting lines.

For enhanced customization, various CRI (Color Rendering Index) and CCT (Correlated Color Temperature) options are available upon request, allowing designers to create the perfect lighting atmosphere.

Linear Rigid module MCPCB/OSRAM with Push in connectors.

Product has the structure and appearance Ensures UGR<19.

24V/48VDC Power Supply for RGB, RGB DMX, RGBW and RGBW DMX.

Optics material: PMMA Opal Diffuser / Micro Prismatic Lens / Prism Lens + Optics Diffusion. sheet, all diffusers and lens are UV stabilized, no inclusions or scratches on the surface.

Standard Length: 990 mm / 1200 mm / 1480 mm / 1970 mm /2100mm

Other lengths can be customized as per design.

Technical Specifications:

Input Voltage: 220- 240 V AC, 60/50Hz.

Wattage: 28-65W/M

Luminaire Efficacy: 110lm/W

3 STEP Mac Adam

High efficiency, low flicker driver

Driver Brand: OSRAM / VS / LumiLEDs

Lamp Type: Linear Rigid Module

Lamp Brand: OSRAM LED

Operating Temperature: 0°C to 25°C

Glow Wire Test 960° C

Warranty: 5 Years

Life Time: 100,000hrs at ta 25°C

(L80/B10)

Fields of Application:

Retail

Education

Galleries hotels

Living spaces

Installation Method:


Recessed

Wattage(W)/M :	28	35	50	65					
Finish :	White(W)	Black(B)	Silver(S)						
Kelvin* :	2700K RGB	3000K RGBW	3500K	4000K	5000K	5700K	6500K	Tunable	
Beam Angle :	120°								
CRI :	80+	90+							
Driver :	ON/OFF	0/1-10V	DALI	Bluetooth	Casambi				

*Special Color & Finish on request

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Color Temperature :




Product Code (9741008865):

Wattage/M	Lumens(LM)	Dimension(W x H) mm
28	3,080LM	100x88
35	3,850LM	100x88
50	5,500LM	100x88
65	7,150LM	100x88

*Luminous flux value is calculated for 4000K & CRI>90.

*Above mentioned wattages can be customized according to designed requirement.

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 9741008865 27K 120D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	120D - 120°	8->80	1 - ON/OFF	W-White
30K - 3000K		9->90	2 - 0/1-10V	B-Black
35K - 3500K			3 - DALI	S-Silver
40K - 4000K			4 - Bluetooth	
50K - 5000K			5 - Casambi	
57K - 5700K				
65K - 6500K				
TuK - Tunable				
RGK - RGB				
RGK - RGBW				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C