



## LONER 48



Accessories:

Suspension Kit



Mounting Clips



### Features:

LONER 48 Linear Extruded Aluminum Profile with highest standard 6063-T6 aluminum, deep anodizing (more than 12µm) that protects against corrosion and extends durability, Matt surface treatment.

Opal PC Diffuser / Micro Prismatic Lens / Prism Lens + Optics Diffusion sheet, all diffusers and lens are UV stabilized, no inclusions or scratches on the surface.

Continues Seamless diffuser up to 30mm length.

Standard Length with Zagha Linear Modules 570 mm / 1200 mm/ 1480 mm/ 1920mm, tailored length can be manufactured as per design.

Homogenous, well-balanced light dispersing with no shadow.

### Technical Specifications:

Input Voltage: 220- 240 V AC, 50 Hz.

Wattage /M: 20 - 65W

Efficacy: 145lm/w

3 STEP Mac Adam

High Efficiency, Low Flicker Driver

Lamp Type: Linear SMD VS Rigid Module

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at ta 25°C  
(L90/B10)

### Fields of Application:

Retail

Education

Galleries hotels

Living spaces

### Installation Method:

Recessed / Suspended.

Wattage(W)	:	20	38	45	60	65	
Finish	:	White(W)	Black(B)	Silver(S)	Customized		
Kelvin*	:	2700K	3000K	3500K	4000K	5000K	Tunable
Beam Angle	:	120°					
CRI	:	80+	90+	Tunable			
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming	Bluetooth	

\*Special Color & Finish on request

### Product Code (964487865):


Wattage	Lumens(lm)	Dimension(W XH) mm	Dimension (L) mm
20	2900 LM	48x78	990
38	5510 LM	48x78	1200
45	6525 LM	48x78	1480
60	8700 LM	48x78	1970
65	9425 LM	48x78	2110

\*Luminous flux value is calculated for 4000K CRI>80

\* Length and Wattage can be customized as per design

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

## Photometric:



### Standards

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 964487865 27K 120D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	120D - 120°	8->80	1 - ON/OFF	W-White
30K - 3000K		9->90	2 - 0/1-10V	B-Black
35K - 3500K		T->Tunable	3 - DALI	S-Silver
40K - 4000K			4 - Phase Dimming	C-Customized
50K - 5000K			5 - Bluetooth	
TuK - Tunable				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C