
pluxb

IP67 IK08

LUKE





Description:

LUKE series of high-power LED wall washers combines sophisticated design with advanced thermal management, thereby ensuring fixture stability and prolonged operational lifespan. The fixture's housing is precision-molded from premium 6063 aluminum alloy and finished with an anodized coating, providing exceptional durability and corrosion resistance. Available in Metallic Gray (RAL9023) with a high-gloss liquid coating and high-temperature grilling, the fixture also offers a 50µm liquid coating to enhance heat dissipation and lifespan, or a 120µm RAL7011 metallic grey powder coating for robust UV protection. With THD less than 10% and a power factor greater than 0.9, it ensures high electrical efficiency and superior performance. The toughened glass surface offers high hardness and impact resistance, and the series provides various CCT options, C5 Marine Grade Coating, Honeycomb, and Anti-glare shield options, making it a versatile solution for diverse project specifications. Customizable lengths include 250mm, 500mm, 750mm, and 1.5m. These fixtures are ideally suited for accentuating architectural elements, illuminating pathways, and enhancing the ambiance of outdoor environments.

Product Specifications:

Housing : Die cast Aluminum
Glass : Tempered glass
Coating : Powder Coating / Liquid Coating
Light Source: Osram / Cree / LumiLeds
Gasket: Molding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Surface Mounted
Adjustable : Yes

Technical Specifications:

Wattage: 30 - 100W
Voltage: 24VDC / 220-240VAC
Frequency: 50-60Hz
Lumen: RGBW (3000K) - 50lm/W
Mac Adam: 3 Step
Safety Class: III
Working Temperature:-25°C to 50°C
Life Time: 50,000hrs (L80/B10) at 25°C
Humidity : <95%
Warranty: 5 Years

Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3

Parameter:

Wattage(W)	:	30W / 50W / 100W
Finish	:	Black (B) / White (W)
Kelvin*	:	RGBW / RGBW DMX
Beam Angle	:	9° / 15°/ 20°/ 30°/ 45° / 15x60°
CRI	:	80+
Control Mode	:	ON/OFF DALI DMX

*Lumen values are calculated at 30° beam angle, 4000K color temperature and CRI 80.

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5426112	30-30W (300mm)	92-RGBW	D - 24VDC	09-9°	B-Black	1-ON/OFF
	50-50W (500mm)	93-RGBW DMX		15-15°	W-White	2-DALI
	100-100W (1000mm)			20-20°		3-DMX
				30-30°		

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

40-40°
15x60-15x60°

Ex: Order Code: 54261123092D'09B1

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5426112	30-30W (300mm)	92-RGBW	A - 220-240VAC	09-9°	B-Black	1-ON/OFF
	50-50W (500mm)	93-RGBW DMX		15-15°	W-White	2-DALI
	100-100W (1000mm)			20-20°		3-DMX
				30-30°		
				40-40°		
				15x60-15x60°		

Ex: Order Code: 54261123092A'09B1

Photometric:

