


LUSTRA



Features:

LUSTRA sleek design, durably, and high-performance surface.
Die cast aluminum body soft design and low glare reflector, with high-quality PC diffuser, renowned for its superior optical clarity and durability.
Engineered to minimize glare and ensure uniform light distribution Interchangeable reflectors with different beam angles and add-on glass diffuse.
The product Lens can 355D Rotate 25D Tilt.
UGR <19 this spotlight sets a new standard in visual comfort.
Where innovation meets elegance to illuminate spaces with unparalleled brilliance and comfort.

Technical Specifications:

Input Voltage: 220- 240 V AC, 60/50Hz.
Wattage: 8 - 12W
High Lumen: 90lm/w
Light source: Citizen CLU02Q-1202
3 STEP Mac Adam
High efficiency, low flicker driver
Lamp Type: COB
Operating Temperature: -20°C to 45°C
Glow Wire Test 850° C
Warranty: 5 Years
Life Time: 50,000hrs at ta 25°C
(L90/B10)

Fields of Application:

Retail
Education
Galleries hotels
Living spaces

Installation Method:

Surface Mounted.

Wattage(W)	:	8	10	12
Finish	:	White(W)	Black(B)	
Kelvin*	:	2700K	3000K	4000K
Beam Angle	:	24°	36°	60°
CRI	:	90+		
Driver	:	ON/OFF	0/1-10V	DALI Phase Dimming


*Special Color and Finish on request

Product Code (97709512):

Wattage	Lumens(lm)	Dimension(Ø x H) mm
8	720LM	98x165
10	900LM	98x165
12	1080LM	98x165

*Luminous flux value is calculated for 4000K CRI>90

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C

- Standards
- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 97709512 27K 24D 9 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	24D - 24°	9->90	1 - ON/OFF	W-White
30K - 3000K	36D - 36°		2 - 0/1-10V	B-Black
40K - 4000K	60D - 60°		3 - DALI	
			4 - Phase Dimming	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C