


MAEVE



Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Description:

MAEVE is a surface-mounted LED step light is designed with a robust die-cast aluminum housing, offering excellent durability and effective heat dissipation for reliable long-term performance.

Its compact and contemporary design provides comfortable, low-glare illumination while adding a subtle architectural accent to the space.

The fixture is well suited for illuminating stairs, pathways, corridors, terraces, entrances, and other indoor or outdoor areas where safe and discreet step lighting is required.

Product Specifications:

Housing : Die cast Aluminium

Diffuser : Frosted PMMA

Coating : Powder Coating

Light Source: Osram / Cree

Gasket: Molding shaped silicone seal

Lens/Reflector : Optical lens (efficiency>90%)

Power Cable: 0.5 mt. power cable included

Driver : High efficiency, low flicker driver

Installation Type: Wall Mounted

Adjustable: No

Technical Specifications:

Wattage: 3W

Voltage: 220-240VAC

Frequency: 50-60Hz

Lumen: 58lm/W

Mac Adam: 3 Step

Safety Class: III

Working Temperature:-20°C to 55°C

Life Time: 50,000hrs (L80/B10) at 35°C

Warranty: 5 Years

Parameter:

Wattage(W)	:	3W
Finish	:	Grey (G) / Black (B) / White (W)
Kelvin*	:	2700K / 3000K / 4000K / 6000K
Beam Angle	:	70°
CRI	:	80+ 90+
Control Mode	:	ON/OFF / DALI

*Lumen values are calculated at 70° beam angle, 4000K color temperature and CRI 80.


Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540117	03 - 3W	27-2700K	A-220-240VAC	70 - 70°	G-Grey	1-ON/OFF
		30-3000K			B-Black	2-DALI
		40-4000K			W-White	
		60-6000K				

Ex: Order Code: 5401170327A'70G1

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C