


MAEVE



Description:

MAEVE is a surface-mounted LED step light is designed with a robust die-cast aluminum housing, offering excellent durability and effective heat dissipation for reliable long-term performance.

Its compact and contemporary design provides comfortable, low-glare illumination while adding a subtle architectural accent to the space.

The fixture is well suited for illuminating stairs, pathways, corridors, terraces, entrances, and other indoor or outdoor areas where safe and discreet step lighting is required.

Product Specifications:

Housing : Die cast Aluminium
 Diffuser : Tempered Glass
 Coating : Frosted PMMA
 Light Source: Osram / Cree
 Gasket: Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Wall Mounted
 Adjustable: No

Technical Specifications:

Wattage: 3W
 Voltage: 220-240VAC
 Frequency: 50-60Hz
 Lumen: 58lm/W
 Mac Adam: 3 Step
 Safety Class: III
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Years

Parameter:

Wattage(W)	:	3W
Finish	:	Grey (G) / Black (B) / White (W)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	70°
CRI	:	80+ 90+
Control Mode	:	ON/OFF DALI

*Lumen values are calculated at 70° beam angle, 4000K color temperature and CRI 80.

Standards :

EN 60598-1
 EN 60598-2-2
 EN 60598-3-2
 EN 60598-3-3


Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540119	03 - 3W	27-2700K 30-3000K 40-4000K 60-6000K	A-220-240VAC	70 - 70°	G-Grey B-Black W-White	1-ON/OFF 2-DALI

Ex: Order Code: 5401190327A'70G1

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C