
pluxb

IP66 IK07

MARQ





Description:

MARQ Bollard is a modern outdoor bollard features a metal body with a top section where the light would likely be emitted, provide lighting for high efficiency and vandal resistance with anti-glare plate .
Tamper proof fixings for increased vandal resistance, weather-resistant housings suitable for outdoor use. Excellent heat dissipation.
It include features such as corrosion resistance , dustproof, anodized and polished, sand blasted, not easy to rust and fade.
It comes with different CCT LED sources and finishes, this family is a perfect solution to the requirement.
This type of fixture is often used for pathway, landscape lighting, Parking lots , Park And Garden due to its minimalist, contemporary style.

Available Height Options: 550mm , 800mm , 1000mm.

Product Specifications:

Housing : Die cast Aluminium
Diffuser : Tempered Glass
Coating: Powder Coating
Gasket: Moulding shaped silicone seal
Power Cable: 0.5 mtr. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Surface Mounted
Adjustable: No
Warranty: 5 Years

Technical Specifications:

Wattage: 8-12W
Voltage: 220-240VAC
Frequency: 50-60Hz
Light Source: Osram / Cree
Lumen: 100lm/W
Mac Adam: 3 Step
Safety Class: III
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C

Parameter:

Wattage(W)	:	8W / 12W
Finish	:	Brushed Stainless Steel (SS)
Kelvin*	:	2700K/ 3000K / 4000K / 5000K / 6000K
Beam Angle	:	180°
CRI	:	80+
Control Mode	:	ON/OFF / DALI

Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3


Order Code:

Product Code	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
547160	08 - 08W 12-12W	27-2700K 30-3000K 40-4000K 50-5000K 60-6000K	A - 220 - 240VAC	180-180°	SS - Stainless Steel	1-ON/OFF 2-DALI

Ex: Order Code: 5471600827A'180SS1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C