pluxb

IP65 IK08

MAYA

Features:

MAYA IP65 is an outdoor/ indoor light. It's a 304 stainless steel base, ensuring exceptional durability and resistance to corrosion.
The PC/glass cover offers both clarity and protection, providing optimal light diffusion while maintaining a sleek, modern aesthetic.
A steel or aluminum reflector enhances light efficiency, maximizing brightness while minimizing energy consumption. The S/S clips design allows for easy and secure installation, making it both user-friendly and sturdy. Equipped with quick connectors this light reduces labor costs by 30%, streamlining the installation process.
An LED T8 tube, which delivers energy-efficient, long-lasting illumination with superior performance. Its super large and wide body size this light covers a broader area, ensuring even and powerful light distribution,

Technical Specifications:

Input Voltage : 220- 240 VAC, 50-60Hz.
Wattage : 2x30 W
High Lumen : 100lm/W
3 STEP Mac Adam
High efficiency, low Flicker Philips driver
Lamp Type : Linear Rigid Modules
Light Source : Bridgelux SMD
Operating Temperature: -20°C to 50°C
Glow Wire Test 850° C
Warranty : 5 Years
Life Time : 50,000hrs at ta 25°C (L80/B10)

Fields of Application:

Offices
Warehouses
Schools
Workstations
Corridors
Hospitals
Sheds

Installation Method:

Surface/Suspended

Wattage(W)/M	:	2x30				
Finish	:	White(W)				
Kelvin*	:	3000K	4000K	5000K	6000K	6500K
Beam Angle	:	120°				
CRI	:	70+	80+			
Driver	:	ON/OFF	0/1-10V	DALI		

*Special Color & Finish on request

Product Code (9601909030):

Wattage/M	Lumens(LM)	Dimension(LxWxH) mm
2x30	6000LM	1600x190x90

*Luminous flux value is calculated for 4000K and CRI>80.
*Above mentioned wattages can be customized according to designed requirement.

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Photometric:



Standards
EN 60598-1
EN 60598-2-2
EN 60598-2-22
EN 60598-3-2
EN 60598-3-3

Order Code Ex: 9601909030 30K 120D 7 1 W

CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	120D - 120°	7->70	1 - ON/OFF	W-White
40K - 4000K		8->80	2 - 0/1-10V	
50K - 5000K			3 - DALI	
60K - 6000K				
65K - 6500K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C