


MIKE



Description:

MIKE is a LED floodlight with its narrowest beam angle achieved through batch production, making it ideal for meeting the demanding requirements of 350m super high-rise architectural lighting and intricate lasso bridge illumination.

Equipped with a professional optical lens, it delivers precise light projection to target objects with maximum efficiency.

Constructed using an extrusion moulding process, it prevents deformation and glass leakage caused by temperature fluctuations, ensuring durability. The built-in highly efficient power, while rigorous quality testing, including a 48-hour aging test at 80°C and 85% humidity.

A waterproof light-transmitting valve prevents condensation within the lamp cavity, balancing internal and external pressure to maintain clear visibility and performance.

It has very wide application like trees, sign terraced landscape, urban lighting, internal and external walls of buildings, etc.

Product Specifications:

Housing : Die cast aluminium
 Coating: Powder Coating
 Diffuser : Tempered glass
 Gasket: Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 No. of LEDs : 24 LEDs
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Surface Mounted

Technical Specifications:

Wattage: 15W
 Voltage: DC24V
 Frequency: 50-60Hz
 Light Source: CREE XML 1 PCS
 Lumen: 80lm/W
 Mac Adam: 3 Step
 Safety Class: III / II
 Working Temperature:-40°C to 50°C
 Life Time: 50,000hrs (L90/B60) at 35°C
 Warranty: 5 Years

Parameter:


Wattage(W)	:	15W
Finish	:	Silver Grey (Sg) / Dark Grey (Dg)/ Black (B) / Customized (C)
Kelvin*	:	1700K/ 2200K/ 2700K/ 3000K/ 4000K/ 6000K/ 6500K
Beam Angle	:	3° / 5°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Bluetooth

Order Code:

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
545163	15-15W	17-1700K	D-24VDC	3 - 3°	Sg-Silver Grey	1-ON/OFF
		22-2200K			Dg-Dark Grey	2-DALI
		27-2700K		5 - 5°	B-Black	3-0/1-10V
		30-3000K			C-Customized	4- Bluetooth
		40-4000K				
		60-6000K				

Ex: Order Code: 5451631517D'3Sg1

Photometric :



- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C