


MILLS



Description:

MILLS is a modern Up-Down decorative wall-mounted LED light fixture with a minimalist design. The light source is positioned at the downward and upward direction. It is typically installed on vertical surfaces such as walls to create a balanced and aesthetically pleasing lighting effect. These lights often contribute to ambient lighting and can enhance the visual appeal of indoor or outdoor spaces. They come in various designs, wattages, and light sources, providing flexibility for different lighting preferences and applications. It has very wide application like For enhance architectural features and provide ambient lighting in residential and commercial spaces, adding both style and functionality.

Product Specifications:

Housing : Die cast Aluminium
Diffuser : Tempered Glass
Reflector : Anodized Aluminium
Gasket: Moulding shaped silicone seal
Power Cable: 0.5 mt. power cable
Driver : High efficiency, low flicker driver
Installation Type: Wall mounted
Adjustable: No

Technical Specifications:

Wattage: 10 - 30W
Voltage: 220-240VAC, 50-60Hz
Light Source: OSRAM / CREE
Lumen: 100lm/W
Mac Adam: 3 Step
Safety Class: III
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	: 10W / 15W / 20W / 30W
Finish	: Grey (G) /Customized (C)
Kelvin*	: 2700K/ 3000K/ 4000K/ 6000K
Beam Angle	: 60°
CRI	: 80+ 90+
Control Mode	: ON/OFF / DALI / 0 / 1-10V

Photometric:

Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540106	10 - 10W (1x10W)	27-2700K	A-220-240VAC	60-60°	G-Grey	1-ON/OFF
	15 - 15W (1x15W)	30-3000K			C-Customized	2-DALI
	20 - 20W (2x10W)	40-4000K				3-0/1-10V
	30 - 30W (2x15W)	60-6000K				

Ex: Order Code: 5401061027A'60G1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C