

## MILO



### Features:


MILO is a Fixture which is designed for durable and efficient outdoor lighting. Its die-cast aluminum housing with a fluorine-sprayed surface provides shockproof and corrosion-resistant performance. The imported anti-aging rubber seal-ring ensures waterproofing and protection. A transparent tempered glass lamp enhances light transmission and durability. It comes in Metallic Gray (RAL9023) with liquid coating, high-temperature grilling, a glossy finish of 20µm, offering good durability, long-lasting performance (up to 10 years), and meeting high requirements for a sense of quality. Its also comes with adjustable bracket Base, Round Base and Stand Base. The honeycomb, Round-meshed grill and Anti glare can make your lighting more dramatic or cinematic. Toughened glass surface, with high hardness, not easy to break. Adopt Imported CREE original LED light source. With gradual temperature increase, excellent heat dissipation, and waterproof sealing. C5 Marine Grade Coating available on request. This Fixture light offers stable and reliable performance for outdoor applications.

### Product Specifications:

Housing : Die cast aluminum  
 Front cover : PMMA  
 Coating : Liquid Coating  
 Glass : 6mm Tempered Glass  
 Gasket : Molding shaped silicone seal  
 Lens/Reflector : Optical lens (efficiency>90%)  
 Power Cable : 0.5 mt. power cable included  
 Driver : High efficiency, low flicker driver  
 Installation Type : Surface Mounted  
 Adjustable : Yes

### Technical Specifications:

Wattage : 150 - 200W  
 Voltage : 100-264VAC  
 Frequency : 50-60Hz  
 Light Source : OSRAM / EPISTAR / CREE  
 Lumen : 100lm/W  
 Mac Adam : 3 Step  
 Safety Class : III  
 Working Temperature : -25°C to 50°C  
 Life Time : 50,000hrs (L80/B10) at 35°C  
 Warranty : 5 Years



### Parameter:

Wattage(W) : 150W / 180W / 200W

Finish : Black (B) / White (W) / Grey (G) / Customized (C)

Kelvin\* : RGBWCLA

Beam Angle : 15° / 20° / 30° / 45° / 15°x60°

CRI : 80+

Driver : ON/OFF / DMX

### Order Code :

Product Code	Type	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
545322	6 - Clamp	150 - 150W	97- RGBWCLA	A - 100 - 264VAC	15 - 15°	B-Black	1-ON/OFF
		180 - 180W			20 - 20°	W-White	2-DMX
		200 - 200W			30 - 30°	G-Grey	
					45 - 45°	C-Customized	
					15x60 - 15x60°		

Ex: Order Code: 545322615097A'15B1

### Type :



### Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C