


MINI



Features:

MINI is fixed recessed spotlight, with die-cast aluminum body and face frame, electrostatic spraying process.

Integrated aluminum material, air convection heat dissipation.

High light Transmissivity.

Homogenous, well-balanced light dispersing, no shadow.

Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.

Wattage: 1W

High Lumen: 115lm/W

3 STEP Mac Adam

High efficiency, low flicker driver

Lamp Type: SMD Chip

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Life Time: 50,000hrs at ta 25°C (L80/B10)

Fields of Application:

Retail

Education

Galleries hotels

Living spaces

Installation Method:

Recessed

Wattage(W)	:	1		
Finish	:	White(W)	Black(B)	
Kelvin*	:	2700K	3000K	4000K
Beam Angle	:	15°		
CRI	:	80+	90+	
Driver	:	ON/OFF	DALI	Casambi


*Special Color and Finish on request

Product Code (96704001):

Wattage	Lumens(lm)	Dimension(ØxH) mm	Cut out (mm)
1	115LM	40x25	30

*Luminous flux value is calculated for 4000K CRI>80

Photometric:



Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96704001 27K 15D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	15D - 15°	8->80	1 - ON/OFF	W-White
30K - 3000K		9->90	2 - DALI	B-Black
40K - 4000K			3 - Casambi	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C