


MINI



Features:

MINI is fixed recessed spotlight, with die-cast aluminum body and face frame, electrostatic spraying process.
 Integrated aluminum material, air convection heat dissipation.
 High light Transmissivity.
 Homogenous, well-balanced light dispersing, no shadow.

Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.
 Wattage: 1W
 High Lumen: 115lm/W
 3 STEP Mac Adam
 High efficiency, low flicker driver
 Lamp Type: SMD Chip
 Operating Temperature: -20°C to 45°C
 Glow Wire Test 850° C
 Warranty: 5 Years
 Life Time: 50,000hrs at ta 25°C (L80/B10)

Fields of Application:

Retail
 Education
 Galleries hotels
 Living spaces

Installation Method:

Recessed

Wattage(W)	:	1		
Finish	:	White(W)	Black(B)	
Kelvin*	:	2700K	3000K	4000K
Beam Angle	:	15°		
CRI	:	80+	90+	
Driver	:	ON/OFF	DALI	Casambi


*Special Color & Finish on request

Product Code (96704601):

Wattage	Lumens(lm)	Dimension(ØxH) mm	Cut out (mm)
1	115LM	46x38	35

*Luminous flux value is calculated for 4000K CRI>80

Photometric:



Standards

- EN 60598-1
- EN 60598-2-2
- EN 60598-2-22
- EN 60598-3-2
- EN 60598-3-3

Order Code Ex: 96704601 27K 15D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	15D - 15°	8->80	1 - ON/OFF	W-White
30K - 3000K		9->90	2 - DALI	B-Black
40K - 4000K			3 - Casambi	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C