


## MOON



### Features:

- MOON Series is surface mounted ceiling light with highly quality of aluminum.
- Body finish available with RAL 9010 offering versatility for different decor styles.
- Heat sink Bottom is Flame-retardant ABS chassis.
- PMMA diffuser, light transmittance up to 90%, uniform light effect, no dark spots, slim design.
- Product has the structure and appearance.
- High thermal conductivity aluminum substrate with SMD LED Chips.
- SENSOR is available as per request.
- Emergency Option is possible for this product.

### Technical Specifications:

- Input Voltage: 220-240 V AC, 50 Hz.
- Wattage: 15-25W
- High Lumen: 120lm/W
- 3 STEP Mac Adam
- High efficiency, low flicker driver
- Lamp Type: SMD
- Lamp Brand: OSRAM
- Driver Brand : KGP / Eaglerise / VS
- Operating Temperature: -25°C to 50°C
- Glow Wire Test 850°C
- Warranty: 5 Years
- Life Time: 100,000hrs at 25°C (L80/B10).

### Fields of Application:

- Retail
- Kitchens
- Corridors
- Conference rooms
- Restaurants
- Lobbies

### Installation Method:

Surface Mounted.

Wattage(W)	:	15	18	23	25
Finish	:	White(W)			
Kelvin*	:	3000K	4000K	5000K	5700K 6500K
Beam Angle	:	120°			
CRI	:	80+	90+		
Driver	:	ON/OFF	DALI		

\*Special Color and Finish on request


### Product Code (96821325):

Wattage	Lumens(lm)	Dimension(Ø x H) mm
15	1800LM	213x63
18	2160LM	213x63
23	2760LM	213x63
25	3000LM	213x63

\*Luminous øux value is calculated for 4000K CRI>80

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

## Photometric:



### Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96821325 30K 120D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	120D - 120°	8->80	1 - ON/OFF	W-White
40K - 4000K		9->90	2 - DALI	
50K - 5000K				
57K - 5700K				
65K - 6500K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C