


NATURE



Description:

NATURE is a Wall Lamp, with simple design and rich texture, composed of stretching aluminum, die-cast aluminum and PC optical parts. The exquisite surface treatment makes the lamp with rich texture and good weather resistance.

The lamp's protection grade is IP65.

It can meet the needs of various applications, with clean spot, comfortable sight and good heat dissipation performance. Waterproof terminals can be built in, which is convenient for installation and maintenance.

It can be used for interior and exterior facade lighting, architectural decorative lighting, etc.

Product Specifications:

Housing : Die cast Aluminium grey
 Diffuser : Clear Glass
 Gasket : Moulding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable : 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Surface mounted
 Adjustable: No

Technical Specifications:

Wattage: 10W
 Voltage: 220-240VAC
 Frequency: 50-60Hz
 Light Source: OSRAM/EPISTAR/CREE
 Lumen: 95lm/W
 Mac Adam: 3 Step
 Safety Class: II
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Years

Parameter:


| | | |
|--------------|---|---|
| Wattage(W) | : | 10W |
| Finish | : | Black (B) / Silver (S) / Customized (C) |
| Kelvin* | : | 3000K / 4000K |
| Beam Angle | : | 360° |
| CRI | : | 80 |
| Control Mode | : | ON/OFF / DALI / 0 / 1-10V |

Order Code:

| Product Code | Wattage | CCT | Voltage | Beam Angle | Finish | Control Mode |
|--------------|---------|----------------------|--------------|------------|-------------------------------------|--------------------|
| 540210 | 10-10W | 30-3000K 40-4000K | A-220-240VAC | 360-360° | B-Black S-Silver C-Customized | 1-ON/OFF 2-DALI |

Ex: Order Code: 5402101030A'360B1

Photometric:



Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C