


NEOMY



Description:

NEOMY is modern LED bollard light combines a distinctive geometric design with reliable outdoor performance, making it ideal for pathways, gardens, landscapes, and residential or commercial outdoor spaces. Constructed with a durable weather-resistant housing and rated IP65, it provides long-lasting protection against dust and water ingress.

It include features such as corrosion resistance , dustproof, anodized and polished, sand blasted, not easy to rust and fade. It comes with different CCT LED sources, Finishes like Corten and C5 Marine coating, this family is a perfect solution to the requirement.

This type of fixture is often used for pathway, landscape lighting, Parking lots , Park And Garden due to its minimalist, contemporary style.

Available Height Options: 500mm, 710mm and 1000mm.

Other heights can be customized.


Product Specifications:

Housing : Die cast Aluminium
Diffuser : Tempered Glass
Coating: Powder Coating
Gasket: Moulding shaped silicone seal
Power Cable: 0.5 mtr. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Surface Mounted
Adjustable: No
Warranty: 5 Years

Technical Specifications:

Wattage: 7-12W
Voltage: 24VDC / 220-240VAC
Frequency: 50-60Hz
Light Source: Bridgelux / OSRAM / CREE
Lumen: 70lm/W
Mac Adam: 3 Step
Safety Class: III
Working Temperature: -30°C to 50°C
Life Time: 50,000hrs (L80/B10) at 35°C

Photometric :



Parameter:

Wattage(W)	: 7W / 10W / 12W
Finish	: RAL 9005 (B) / RAL 7001 (S) / RAL 8011 (NB) / RAL 8003 (CB)
Kelvin*	: 2700K/ 3000K / 4000K / 5000K / 6000K
Beam Angle	: Asymmetric
CRI	: 80+ 90+
Control Mode	: ON/OFF / DALI

Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3

Order Code:

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
547140	07-7W	27-2700K	D - 24VDC	AS - Asymmetric	B - RAL 9005	1-ON/OFF
	10-10W	30-3000K			S - RAL 7001	2-DALI
	12-12W	40-4000K			NB - RAL 8011	
		50-5000K			CB - RAL 8003	
		60-6000K				

Ex: Order Code: 5471400727D'ASB1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C