



NEVE'S



Description:

NEVE'S is an IP68 inground light is a durable lighting fixture designed to be installed below ground level, typically used for outdoor or landscape lighting.

It is highly durable and versatile light with an Ingress Protection (IP) rating of 68. This rating signifies complete protection against dust and allows the lights to be submerged in water beyond 1 meter.

It comes with different CCT and various beam angles this family is a perfect solution to the requirement.

Ideal for challenging environments, IP68 lights are resilient, making them suitable for outdoor, marine, and demanding applications, ensuring reliable performance in harsh conditions.

Product Specifications:

Housing : Stainless steel 316
 Front cover : Stainless steel 316
 Glass : Clear glass
 Gasket: Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Under Water (Inground)
 Adjustable: No

Technical Specifications:

Wattage: 2.5W
 Voltage: DC24V
 Light Source: OSRAM/EPISTAR/CREE
 Lumen: 80lm/W
 Mac Adam: 3 Step
 Safety Class: III
 Cut Out : D31*H40
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Years

Parameter:


| | | |
|--------------|---|---------------------------------------|
| Wattage(W) | : | 2.5W |
| Finish | : | Stainless Steel 316 (SS) |
| Kelvin* | : | 2700K/ 3000K/ 4000K/ 6000K /RGB /RGBW |
| Beam Angle | : | 37° |
| CRI | : | 80+ |
| Control Mode | : | ON/OFF / DALI / 0 / 1-10V |

Order Code:

| Product Code | Wattage | CCT | Voltage(DC) | Beam Angle | Finish | Control Mode |
|--------------|---------|----------|-------------|------------|------------------------|--------------|
| 546042 | 02-2.5W | 27-2700K | D-24VDC | 37-37° | SS-Stainless Steel 316 | 1-ON/OFF |
| | | 30-3000K | | | | 2-DALI |
| | | 40-4000K | | | | 3-0/1-10V |
| | | 60-6000K | | | | |

Ex: Order Code: 5460420227D'37SS1

Photometric:



Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C