



NORMA



Wire comes out from a back



**Description:**

NORMA is a modern linear light is made from extruded aluminum ensuring durability and efficient heat dissipation. Diffuser choices include Opal PC diffuser or PMMA PC diffuser for enhanced light distribution and glare control. Installation options include magnetic strip or surface mounted Clip, offering flexibility for various applications. Product has the structure and appearance. Ensures UGR<19 for PMMA diffuser. The standard length are 500mm, 750mm, 1mtr & 1.2mtr. Customization available upon request. They are commonly used for accentuating architectural features, guiding pathways, or creating ambiance in outdoor spaces.

**Product Specifications:**

Housing : Extruded Aluminum  
 Diffuser : PMMA  
 High efficiency, low flicker driver  
 Chip Brand : OSRAM / Samsung / CREE  
 Driver Brand: OSRAM / VS / Tridonic  
 Installation: Magnetic Strip /  
 Surface Mounted Clips

**Technical Specifications:**

Wattage: 20-36W  
 Voltage: DC24V  
 Frequency: 50/60Hz  
 High Lumen: 80m/W  
 Lumens(lm): 1600LM-2880LM  
 Mac Adam: 3 Step Mac Adam  
 Safety Class: III  
 Working Temperature: -25°C to 60°C  
 Life Time: 50,000hrs (L80/B10)  
 Humidity : <95%  
 Warranty: 5 Years


**Parameter:**

Wattage(W)	: 20W / 36W
Finish	: Grey (G) / White (W) / Black (B)
Kelvin*	: 2700K/ 3000K/ 4000K/ 6500K
Beam Angle	: 120°
CRI	: 80+ 90+
Control Mode	: ON/OFF / DALI / 0 / 1-10V

**Order Code:**

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
9642219	20 - 20W	27-2700K	D-24VDC	120-120°	G - Grey	1-ON/OFF
	36 - 36W	30-3000K			W - White	2-DALI
		40-4000K			B-Black	3-0/1-10V
		65-6500K				

**Photometric:**



**Standards :**

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C