


## NOVA



### Description:

NOVA is wall-mounted light fixture with three LED elements encased in a protective housing. The design suggests it is intended for outdoor or industrial use, providing focused or widespread illumination. The sturdy casing likely protects the light elements from environmental factors such as rain, dust, or impact.

They come in various designs, wattages, and light sources, providing flexibility for different lighting preferences and applications.

It has very wide application like For enhance architectural features and provide ambient lighting in residential and commercial spaces, adding both style and functionality.

### Product Specifications:

Front cover : Die cast Aluminium grey  
 Housing : Die cast Aluminium grey  
 Diffuser : Glass lenses  
 Gasket: Moulding shaped silicone seal  
 Lens/Reflector : Optical lens (efficiency>90%)  
 Power Cable: 0.5 mt. power cable included  
 Driver : High efficiency, low flicker driver  
 Installation Type: Surface mounted  
 Adjustable: No

### Technical Specifications:

Wattage: 6-9W  
 Voltage: 220-240VAC  
 Frequency: 50-60Hz  
 Light Source: OSRAM/EPISTAR/CREE  
 Lumen: 100lm/W  
 Mac Adam: 3 Step  
 Safety Class: II  
 Working Temperature:-20°C to 55°C  
 Life Time: 50,000hrs (L80/B10) at 35°C  
 Warranty: 5 Year

### Parameter:


Wattage(W)	:	6W / 9W
Finish	:	Grey (G) /Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	8° / 15° / 25° / 40° / 60°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut

### Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540124	06-6W(3x2W)	27-2700K	A-220-240VAC	8-8°	G-Grey	1-ON/OFF
	09-9W(3x3W)	30-3000K		15-15°	C-Customized	2-DALI
		40-4000K		25-25°		3-0/1-10V
		60-6000K		40-40°		4-Phase cut
			60-60°			

**Ex: Order Code:** 5401240627A'8G1

### Photometric:



### Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C