


## NYLO



### Description:

NYLO is a type of IP65 wall-mounted light fixture. The IP65 rating indicates that the light is protected against dust and low-pressure water jets, making it suitable for outdoor use.

As it can withstand harsh weather conditions like rain and humid environments, providing durability and resistance to corrosion over time.

The housing design likely incorporates mechanisms for heat dissipation, ensuring the LED lights inside maintain optimal performance over long periods.

IP65 rating are suitable for various applications, including outdoor spaces, bathrooms, corridors, and industrial environments.

### Product Specifications:

Housing : Die cast Aluminium  
 Diffuser : Tempered glass.  
 Gasket: Moulding shaped silicone seal  
 Lens/Reflector : Optical lens (efficiency>90%)  
 Power Cable: 0.5 mt. power cable included  
 Driver : High efficiency, low flicker driver  
 Installation Type: Wall mounted  
 Adjustable: No  
 Warranty: 5 Years

### Technical Specifications:

Wattage: 10W  
 Voltage: 220-240VAC  
 Frequency: 50-60Hz  
 Light Source: OSRAM/EPISTAR/CREE  
 Lumen: 100lm/W  
 Mac Adam: 3 Step  
 Safety Class: II  
 Working Temperature:-20°C to 55°C  
 Life Time: 50,000hrs (L80/B10) at 35°C

### Parameter:


Wattage(W)	:	10W
Finish	:	Black (B) / White (W) / Grey (G)
Kelvin*	:	2700K/ 3000K / 4000K / 5000K/ 6000K
Beam Angle	:	15° / 24° / 38°
CRI	:	80 / 90
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut

### Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540103	10-10W (SMD)	27-2700K	A-220-240VAC	15-15°	B-Black	1-ON/OFF
		30-3000K		24-24°	W-White	2-DALI
		40-4000K		38-38°	G-Grey	3-0/1-10V
		50-5000K				4-Phase cut
		60-6000K				

**Ex: Order Code:** 5401031027A'15B1

### Photometric:



### Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C