



OCSI



Description:

OCSI is a wall recessed light fixture. It is designed to be installed flush with the wall, providing a sleek and modern look.

The light source is likely concealed within the fixture, emitting light through the elliptical opening in the center.

This design is often used for ambient or accent lighting in various indoor and outdoor settings. It includes features such as corrosion resistance, dustproof, anodized and polished, sandblasted, not easy to rust and fade.

It is ideal for providing ambient or accent lighting in residential or commercial spaces, such as hallways, staircases, and outdoor walkways.

Product Specifications:

Front cover : Die cast aluminium Grey
Housing : Die cast aluminium Grey
Coating: Powder Coating
Gasket: Moulding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Wall Recessed
Adjustable: No

Technical Specifications:

Wattage: 2- 3W
Voltage: 220-240V AC
Frequency: 50-60Hz
Light Source: OSRAM/EPISTAR/CREE
Lumen: 100lm/W
Mac Adam: 3 Step
Safety Class: II
Working Temperature: -20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:


Wattage(W)	:	2W / 3W
Finish	:	Grey (G) / Customized (C)
Kelvin*	:	2700K / 3000K / 4000K / 6000K
Beam Angle	:	80°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V
Type	:	Round (R) / Square(S)

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539089	02-2W(1X2W)	27-2700K	A-240-220VAC	80-80°	G- Grey	1-ON/OFF
	03-3W(1X3W)	30-3000K			C-Customized	2-DALI
		40-4000K				3-0/1-10V
		60-6000K				

Ex: Order Code: 5390890227A'80G1

Photometric :



Standard :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3