




OILEY



Description:

OILEY is a wall recessed step light is designed to provide subtle, glare-free illumination while integrating seamlessly into the wall surface.

Constructed from durable die-cast aluminum with a protective finish, providing excellent strength and corrosion resistance for long-lasting performance.

Toughened glass and a durable sealing system provide reliable protection for both indoor and outdoor applications.

Fully recessed installation keeps the luminaire discreet and flush with the wall, minimizing visual obstruction while enhancing architectural aesthetics.

Suitable for stairways, walkways, corridors, entrances, landscape pathways, terraces, hotels, residential areas, and commercial spaces.

Product Specifications:

Front cover : Die cast Aluminium
Housing : Die cast Aluminium
Diffuser : Tempered Glass
Coating : Powder Coating
Light Source: OSRAM
Gasket: Molding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Wall Recessed
Adjustable: No

Technical Specifications:

Wattage: 5.8W
Voltage: 220-240VAC
Frequency: 50-60Hz
Lumen: 55lm/W
Mac Adam: 3 Step
Safety Class: III
Cut Out : L76xW76xH60
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	5.8W
Finish	:	Grey (G) / Black (B) / White (W) / Customized (C)
Kelvin*	:	2700K / 3000K / 4000K / 6000K
Beam Angle	:	100°
CRI	:	80+ 90+
Control Mode	:	ON/OFF DALI

*Lumen values are calculated at 100° beam angle, 4000K color temperature and CRI 80.

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539081	05 - 5.8W	27-2700K	A-220-240VAC	100-100°	G-Grey	1-ON/OFF
		30-3000K			B-Black	2-DALI
		40-4000K			W-White	
		60-6000K			C-Customized	


Ex: Order Code: 5390810527A'100G1

Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C