


OLIVO



Description:

OLIVO is a type of indoor and outdoor linear recessed light fixture.

The IP65 rating indicates that the light is protected against dust and low-pressure water jets. As it can withstand harsh weather conditions like rain and humid environments, providing durability and resistance to corrosion over time.

The product made of die cast aluminum body with temperature glass diffuser for enhanced durability in demanding environment.

The housing design likely incorporates mechanisms for heat dissipation, ensuring the LED lights inside maintain optimal performance over long periods.

IP65 rating are suitable for various applications, including outdoor spaces, bathrooms, corridors, and industrial environments.

Product Specifications:

Housing : Die cast Aluminium
Diffuser : Tempered glass
Coating : Powder Coating
Light Source: Osram
Gasket: Moulding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Ceiling Recessed
Adjustable: Yes

Technical Specifications:

Wattage: 10-12W
Voltage: 220-240VAC
Frequency: 50-60Hz
Lumen: Single Color (3000K) - 80lm/W
Mac Adam: 3 Step
Safety Class: II
Cut Out : L150*H45mm
Working Temperature:-20°C to 50°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	10W / 12W
Finish	:	Black (B) / White (W)
Kelvin*	:	2700K/ 3000K / 4000K / 5000K/ 6000K
Beam Angle	:	15° / 24° / 38°
CRI	:	80+ 90+
Control Mode	:	ON/OFF DALI

*Lumen values are calculated at 38° beam angle, 3000K color temperature and CRI 90.

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539158	10-10W	27-2700K	A-220-240VAC	15-15°	B-Black	1-ON/OFF
		30-3000K		24-24°	W-White	2-DALI
	12-12W	40-4000K		38-38°		
		50-5000K				
		60-6000K				

Ex: Order Code: 5391581027A'15B1

Standards :

EN 60598-1




EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C