


OLIVO



Description:

OLIVO is a type of IP65 linear recessed light fixture. The IP65 rating indicates that the light is protected against dust and low-pressure water jets, making it suitable for outdoor use.

As it can withstand harsh weather conditions like rain and humid environments, providing durability and resistance to corrosion over time.

The housing design likely incorporates mechanisms for heat dissipation, ensuring the LED lights inside maintain optimal performance over long periods.

IP65 rating are suitable for various applications, including outdoor spaces, bathrooms, corridors, and industrial environments.

Product Specifications:

Housing : Die cast Aluminium
 Diffuser : Tempered glass.
 Gasket: Moulding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Recessed
 Adjustable: No
 Warranty: 5 Years

Technical Specifications:

Wattage: 10-12W
 Voltage: 220-240VAC
 Frequency: 50-60Hz
 Light Source: OSRAM/EPISTAR/CREE
 Lumen: 100lm/W
 Mac Adam: 3 Step
 Safety Class: II
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C

Parameter:


Wattage(W)	:	10W / 12W
Finish	:	Black (B) / White (W) / Grey(G)
Kelvin*	:	2700K/ 3000K / 4000K / 5000K/ 6000K
Beam Angle	:	15° / 24° / 38°
CRI	:	80 / 90
Control Mode	:	ON/OFF / DALI / 0 / 1-10V / Phase Cut

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539159	10-10W (SMD)	27-2700K	A-220-240VAC	15-15°	B-Black	1-ON/OFF
	12-12W (SMD)	30-3000K		24-24°	W-White	2-DALI
		40-4000K		38-38°	G-Grey	3-0/1-10V
		50-5000K				4-Phase cut
		60-6000K				

Ex: Order Code: 5391591027A'15B1

Photometric:



Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C