


OLIVO



Description:

OLIVO is a type of indoor and outdoor linear recessed light fixture.

The IP65 rating indicates that the light is protected against dust and low-pressure water jets. As it can withstand harsh weather conditions like rain and humid environments, providing durability and resistance to corrosion over time.

The product made of die cast aluminum body with temperature glass diffuser for enhanced durability in demanding environment.

The housing design likely incorporates mechanisms for heat dissipation, ensuring the LED lights inside maintain optimal performance over long periods.

IP65 rating are suitable for various applications, including outdoor spaces, bathrooms, corridors, and industrial environments.

Product Specifications:

Housing : Die cast Aluminum
 Diffuser : Tempered glass
 Coating : Powder Coating
 Light Source: Osram
 Gasket: Molding shaped silicone seal
 Lens/Reflector : Optical lens (efficiency>90%)
 Power Cable: 0.5 mt. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Ceiling Recessed
 Adjustable: Yes

Technical Specifications:

Wattage: 20-24W
 Voltage: 220-240VAC
 Frequency: 50-60Hz
 Lumen: Single Color (3000K) - 80lm/W
 Mac Adam: 3 Step
 Safety Class: II
 Cut Out : L280*H45mm
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Years

Parameter:

Wattage(W)	:	20W / 24W
Finish	:	Black (B) / White (W)
Kelvin*	:	2700K/ 3000K/ 4000K/ 5000K/ 6000K
Beam Angle	:	15° / 24° / 38°
CRI	:	80+ 90+
Control Mode	:	ON/OFF DALI

*Lumen values are calculated at 38° beam angle, 3000K color temperature and CRI 90.

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539290	12 - 12W	27-2700K	A-220-240VAC	15-15°	B-Black	1-ON/OFF
	24 - 24W	30-3000K		24-24°	W-White	2-DALI
		40-4000K		38-38°		
		50-5000K				
		60-6000K				




Ex: Order Code: 5392901227A'15B1

Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C