


OPTIL



Features:

OPTIL is a recessed spotlight, expertly crafted from premium aluminum and finished with a solvent-free powder coating to ensure long-lasting durability and resistance to wear, with PMMA Lens source to shape, control, and direct the beam of light and mounting module, interchangeable.

The fixture structure ensures UGR < 7, delivering comfortable, glare-controlled lighting.

The most classic and practical lamps, super versatile.

Anti-glare reflector options color with White, Black or Chrome.

For enhanced customization, various CRI (Color Rendering Index) and CCT (Correlated Color Temperature) options are available upon request, allowing designers to create the perfect lighting atmosphere.

Structural supports and reflector combination of refined design, advanced optics.

Technical Specifications:

Input Voltage: 220- 240 V AC, 50/60Hz.

Wattage: 10-14W

Efficiency: 90lm/W

High efficiency, low flicker driver

3 STEP Mac Adam

Lamp Type: COB

Operating Temperature: -20°C to 45°C

Glow Wire Test 850° C

Warranty: 5 Years

Lifetime 50,000hrs at a 25°C(L90/B10)

Fields of Application:

Retail
Education
Galleries hotels
Living spaces
Museums
Restaurants
Painting Exhibitions
Theaters

Installation Method:

Recessed


Wattage(W)	:	10	14			
Finish	:	White(W)	Black(B)			
Kelvin*	:	2700K	3000K	3500K	4000K	5700K
Beam Angle	:	21°	31°	43°	52°	
CRI	:	90+				
Driver	:	ON/OFF	DALI	Phase Dimming	1-10V	

*Special Color and Finish on request

Product Code (96707514):

Wattage	Lumens(lm)	Dimension (ØxH) mm	Cut Out  (mm)
10	900LM	75x136	65
14	1260LM	75x136	65

*Luminous flux value is calculated for 4000K CRI>90, 3 STEP Mac Adam



- Standards**
- EN 60598-1
 - EN 60598-2-2
 - EN 60598-2-22
 - EN 60598-3-2
 - EN 60598-3-3

Order Code Ex: 96707514 27K 21D 9 1 W

CCT	Beam Angle	CRI	Driver	Finish
27K - 2700K	21D - 21°	9-	1 - ON/OFF	W-
30K - 3000K	31D - 31°	>90	2 - DALI	White
35K - 3500K	43D - 43°		3 - Phase	B-Black
	52D - 52°		Dimming	
40K - 4000K			4 - 1-10V	
57K - 5700K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C