

pluxb

IP65 IK05

ORCA

LED FLICKER FREE





Description:

ORCA is a outdoor recessed wall light features a compact and minimalist design, ideal for subtle architectural illumination.
The durable aluminium body ensures reliable performance.
With its IP65 protection, it is suitable for outdoor environments.
Available in black and white finishes to complement different architectural styles.
Its sleek appearance blends seamlessly with modern outdoor spaces. Designed for recessed installation, it provides effective lighting for staircases, pathways, and walls.

Product Specifications:

Front cover : Die cast aluminium
Housing : Die cast aluminium
Coating: Powder Coating
Light Source: Osram
Gasket: Moulding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Wall Recessed
Adjustable: No

Technical Specifications:

Wattage: 2- 3W
Voltage: 24VDC
Frequency: 50-60Hz
Lumen: 63lm/W
Mac Adam: 3 Step
Safety Class: III
Cut out : D36xH70mm
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	2W / 3W
Finish	:	Grey (G) / Black (B) / White (W) / Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K
Beam Angle	:	34°
CRI	:	80+
Control Mode	:	ON/OFF / DALI

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539038	02-2W 03-3W	27-2700K 30-3000K 40-4000K 60-6000K	D - 24VDC	34-34°	G- Grey B-Black W-White C-Customized	1-ON/OFF 2-DALI


Ex: Order Code: 5390380227D'34G1

Standard :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C