
pluxb

IP65 IK06

OWEN

LED





Description:

OWEN wall light is a sleek, fully recessed fixture designed to sit flush within the wall, creating a clean and seamless architectural appearance.
Crafted from durable die-cast aluminum, it offers excellent strength and long-term reliability.
Its minimalist form blends naturally into the wall surface while providing comfortable and functional illumination.
Ideal for corridors, stairways, pathways, entrances, and other architectural spaces where discreet lighting is desired.

Product Specifications:

Housing : Die cast Aluminium
Diffuser : Tempered Glass
Coating : Powder Coating
Light Source :Cree / Osram
Gasket: Molding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Wall Recessed
Adjustable: No

Technical Specifications:

Wattage: 3W
Voltage: 24VDC
Frequency: 50-60Hz
Lumen: 80lm/W
Mac Adam: 3 Step
Safety Class: III
Cut Out : L150xW150xD82mm
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C
Warranty: 5 Years

Parameter:

Wattage(W)	:	3W
Finish	:	Grey (G) / Black (B) / Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K
Beam Angle	:	25°/ 45°/ 10*60°
CRI	:	80+ 90+
Control Mode	:	ON/OFF DALI

Standards :

EN 60598-1
EN 60598-2-2
EN 60598-3-2
EN 60598-3-3


Order Code:


Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
539072	03 - 3W	27-2700K	D - 24VDC	25-25°	G-Grey	1-ON/OFF
		30-3000K		45-45°	B-Black	2-DALI
		40-4000K		10*60-10*60°	C-Customized	


Ex: Order Code: 5390720327D'25G1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Photometric:







Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C