










OXO





LED 🕏 🕲 🔉 🖒 🖂 LM-80 🙀 🖍 Flicker













Description:

OXO is a Trimless underground light typically feature durable, weather-resistant housings suitable for outdoor use. Excellent heat dissipation.

It include features such as corrosion resistance, dustproof, anodized and polished, sand blasted, not easy to rust and fade.

Toughened glass surface, with 6mm thickness, not easy to break.

It comes with different CCT and various beam angles this family is a perfect solution to the

It has very wide application like For landscape lighting, garden lighting, horticultural engineering design, public fountain square Lighting.

Product Specifications:

Housing: Die cast aluminum Coating: Powder Coating Glass: Tempered glass Net Weight: 1.2KG

Gasket: Molding shaped silicone seal Lens/Reflector: Optical lens (efficiency>90%) Power Cable: 0.5 mt. power cable included Driver: High efficiency, low flicker driver

Installation Type: Inground

Technical Specifications:

Wattage: 6W Voltage: 24VDC Frequency: 50-60Hz Light Source: CREE Lumen: 95lm/W Mac Adam: 3 Step Safety Class: III

Working Temperature: -20°C to 55°C Life Time: 50,000hrs (L80/B10) at 35°C

Warranty: 5 Years

Parameter:

Wattage(W) : 6W Finish Gray (G) / Black (B) / White (W)

Kelvin* 2700K/3000K/4000K/6000K

Beam Angle 6°/11°/17°/23°/28°/43°/58°/15x30°/15x60° :

CRI 80+

Control Mode : ON/OFF / DALI / 0 / 1-10V

Standard:

EN 60598-1 EN 60598-2-2 EN 60598-3-2

EN 60598-3-3

Order Code:

Product Code	Wattage	CCT	Voltage(DC)	Beam Angle	Finish	Control Mode
544078	6 - 6W	27-2700K	D - 24VDC	6 - 6°	G - Grey	1-ON/OFF
		30-3000K		11-11°	B - Black	2-DALI
		40-4000K		17 - 17°	W - White	3-0/1-10V
		60-6000K		23 - 23°		
				28 - 28°		
				43 - 43°		
				58 - 58°		
				15x30 - 15x30°		
				15x60 - 15x60°		

Ex: Order Code: 544078627D'6G1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C