

PALM



Description:

PALM Bollard is a modern outdoor bollard features a metal body with a top section where the light would likely be emitted, provide lighting for high efficiency and vandal resistance with anti-glare plate .

Tamper proof fixings for increased vandal resistance, weather-resistant housings suitable for outdoor use. Excellent heat dissipation.

It include features such as corrosion resistance , dustproof, anodized and polished, sand blasted, not easy to rust and fade.

It comes with different CCT LED sources and finishes, this family is a perfect solution to the requirement.

This type of fixture is often used for pathway, landscape lighting, Parking lots , Park And Garden due to its minimalist, contemporary style.

Available Height Options: 600mm , 800mm , 1000mm.

Product Specifications:

Housing : Die cast Aluminium
 Diffuser : Polycarbonate
 Coating: Powder Coating
 Gasket: Moulding shaped silicone seal
 Power Cable: 0.5 mtr. power cable included
 Driver : High efficiency, low flicker driver
 Installation Type: Surface Mounted
 Adjustable: No
 Warranty: 5 Years

Technical Specifications:

Wattage: 5W
 Voltage: 220-240V AC
 Frequency: 50-60Hz
 Light Source: Bridgelux / OSRAM
 Lumen: 100lm/W
 Mac Adam: 4 Step
 Safety Class: I
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C

Parameter:


Wattage(W)	:	5W
Finish	:	Sand Black (B) / Sand White (W) / Customized (C)
Kelvin*	:	2700K/ 3000K / 4000K / 5000K / 6000K
Beam Angle	:	100°
CRI	:	80
Control Mode	:	ON/OFF / DALI / 0 / 1-10V

Order Code:

Product Code	Wattage	CCT	Voltage(AC)	Beam Angle	Finish	Control Mode
547040	05-5W	27-2700K	A-220-240VAC	100-100°	B-Sand Black	1-ON/OFF
		30-3000K			W-Sand White	2-DALI
		40-4000K			C-Customized	3-0/1-10V
		50-5000K				
		60-6000K				

Ex: Order Code: 5470400527A100B1

Photometric :



Standards :

EN 60598-1
 EN 60598-2-2
 EN 60598-3-2
 EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C