



MOON

**Features:**

MOON Series is surface mounted ceiling light with highly quality of aluminum. Body finish available with RAL 9010 offering versatility for different decor styles. Heat sink Bottom is Flame-retardant ABS chassis. Acrylic PMMA cover, light transmittance up to 90%, uniform light effect, no dark spots, slim design. Product has the structure and appearance Ensures UGR<19. High thermal conductivity aluminum substrate with SMD LED Chips. Available with Control Protocol: TIMER SWITCH / SENSOR Emergency Option is possible for this product.

Technical Specifications:

Input Voltage: 220-240 V AC, 50 Hz.
 Wattage: 15-25W
 High Lumen: 110lm/W
 3 STEP Mac Adam
 High efficiency, low flicker driver
 Lamp Type: OSRAM 2835 SMD
 Lamp Brand: OSRAM
 Operating Temperature: -25°C to +50°C
 Glow Wire Test 850°C
 Warranty: 5 Years
 Life Time: 50,000hrs at 25°C (L80/B10).

Fields of Application:

Retail
 Kitchens
 Corridors
 Conference rooms
 Restaurants
 Lobbies

Installation Method:

Surface Mounted.


Wattage(W)	15	18	23	25
Finish	White(W)			
Kelvin*	3000K	4000K	5000K	5700K
Beam Angle	90°			
CRI	80+	90+		
Driver	ON/OFF	0/1-10V	DALI	Phase Dimming

*Special Color and Finish on request

Product Code (96821325):

Wattage	Lumens(lm)	Dimension(Ø x H) mm
15	1650LM	213x63
18	1980LM	213x63
23	2530LM	213x63
25	2750LM	213x63

*Luminous flux value is calculated for 4000K CRI>80

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 96821325 30K 90D 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	90D - 90°	8->80	1 - ON/OFF	W-White
40K - 4000K		9->90	2 - 0/1-10V	
50K - 5000K			3 - DALI	
57K - 5700K			4 - Phase Dimming	
65K - 6500K				

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C