


QUAD II



Features:

QUAD II is a Parking light designed for high optical efficiency, delivering up to 90% performance with precise light control.

When paired with luminous polymer-based surfaces, it ensures exceptionally high efficacy and visually comfortable illumination.

The luminaire features an impact-resistant white polycarbonate housing with acrylic lenses, combined with a corrosion-resistant anodized aluminum top plate for long-term durability.

With integrated PIR Motion ON/OFF Sensor.

Its low-profile, lightweight construction simplifies handling and installation while providing uniform, glare-free lighting for modern parking environments.

Technical Specifications:

- Input Voltage: 220-240vAC
- Wattage: 35W
- High Lumen: 125lm/w
- 3 STEP Mac Adam
- High efficiency, low Flicker driver
- Lamp Type: OSRAM 3030
- Operating Temperature: -20°C to 50°C
- Glow Wire Test 850° C
- Warranty: 5 Years
- Life Time: 60,000hrs at 25°C (L70/B10).

Fields of Application:

- Parking garages
- Parking lots
- Underground Parking
- Commercial basements
- Transit stations and terminals
- Industrial warehouses
- Airports and railway stations

Installation Method:

Surface / Suspended

Wattage(W)	:	35			
Finish	:	White(W) Black(B)			
Kelvin*	:	3000K	3500K	4000K	5700K
Beam Angle	:	Type V			
CRI	:	80+	90+		
Driver	:	ON/OFF	0/1-10V	DALI	Phase Dimming


*Special Color and Finish on request

Product Code (96840035):

Wattage	Lumens(lm)	Dimension(W x H) mm
35	4375LM	406x191

*Luminous Lux value is calculated for 4000K and CRI>90

Photometric:



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C

Standards

EN 60598-1

EN 60598-2-2

EN 60598-2-22

EN 60598-3-2

EN 60598-3-3

Order Code Ex: 98840035 30K Type V 8 1 W

CCT	Beam Angle	CRI	Driver	Finish
30K - 3000K	Type V	8->80	1 - ON/OFF	W-White
35K - 3500K		9->90	2 - 0/1-10V	B-Black
40K - 4000K			3 - DALI	
57K - 5700K			4 - Phase Dimming	

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C