


QUIZ



Description:

QUIZ is a outdoor ceiling-mounted applications, this robust cylindrical light combines a clean architectural form with durable construction.

The die-cast aluminium body provides strength and reliability while maintaining a refined, minimalist appearance.

Its compact profile integrates neatly into ceilings, making it suitable for modern outdoor environments where both functionality and aesthetics are important.

Ideal for entrances, covered walkways, terraces, balconies, canopies, hospitality spaces, and other exterior areas, it offers a versatile lighting solution that complements a wide range of contemporary designs.

Product Specifications:

Housing : Die cast Aluminium
 Diffuser : Tempered Glass
 Coating : Powder Coating
 Light Source: Cree
 Gasket: Moulding shaped silicone seal
 Power Cable: 0.5 mt. power cable
 Driver : High efficiency, low flicker driver
 Installation Type: Ceiling mounted
 Adjustable: No

Technical Specifications:

Wattage: 10 - 20W
 Voltage: 220-240VAC, 50-60Hz
 Lumen: 98lm/W
 Mac Adam: 3 Step
 Safety Class: III
 Dimension : D100*H220mm
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Years

Parameter:

Wattage(W)	:	10W / 20W
Finish	:	Black (B) / White (W) / Grey (G)
Kelvin*	:	2700K / 3000K / 4000K / 6000K
Beam Angle	:	15° / 24° / 36° / 45° / 60°
CRI	:	80+ 90+
Control Mode	:	ON/OFF DALI

*Lumen values are calculated at 45° beam angle, 4000K color temperature and CRI 80.






Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540098	10 - 10W	27-2700K	A-220-240VAC	15-15°	B-Black	1-ON/OFF
	20 - 20W	30-3000K		24-24°	W - White	2-DALI
		40-4000K		36-36°	G - Grey	
		60-6000K		45-45°		
				60-60°		

Ex: Order Code: 5400981027A15B1

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C