




QUIZ I



Description:

QUIZ I is a wall-mounted downlight designed for outdoor applications, combining a clean architectural form with durable construction.

Its robust cylindrical design creates a refined and contemporary appearance while providing reliable performance in exterior environments. The die-cast aluminium body offers strength and durability while maintaining a minimalist aesthetic.

Its compact profile integrates neatly onto walls, making it suitable for entrances, covered walkways, terraces, balconies, canopies, hospitality spaces, and other exterior areas where functional and visually appealing illumination is required.

Product Specifications:

Housing : Die cast Aluminium
 Diffuser : Tempered Glass
 Coating : Powder Coating
 Light Source: Cree
 Gasket: Moulding shaped silicone seal
 Power Cable: 0.5 mt. power cable
 Driver : High efficiency, low flicker driver
 Installation Type: Wall mounted
 Adjustable: No

Technical Specifications:

Wattage: 10 - 20W
 Voltage: 220-240VAC, 50-60Hz
 Lumen: 98lm/W
 Mac Adam: 3 Step
 Safety Class: III
 Dimension : D100*H220mm
 Working Temperature:-20°C to 55°C
 Life Time: 50,000hrs (L80/B10) at 35°C
 Warranty: 5 Years

Parameter:

Wattage(W)	:	10W / 20W
Finish	:	Black (B) / White (W) / Grey (G)
Kelvin*	:	2700K / 3000K / 4000K / 6000K
Beam Angle	:	15° / 24° / 36° / 45° / 60°
CRI	:	80+ 90+
Control Mode	:	ON/OFF DALI

*Lumen values are calculated at 45° beam angle, 4000K color temperature and CRI 80.

Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540096	10 - 10W	27-2700K	A-220-240VAC	15-15°	B-Black	1-ON/OFF
		30-3000K		24-24°	W - White	2-DALI
	20 - 20W	40-4000K		36-36°	G - Grey	
		60-6000K		45-45°		
				60-60°		

Ex: Order Code: 5400961027A'15B1

Standards :

EN 60598-1






EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Photometric:

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C



Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C