


## RAME



### Description:

RAME is a outdoor linear wall washer is lighting fixtures designed to provide uniform illumination along the length of a wall or other vertical surfaces.

No IR light source and UV-assisted technology, It also offers directional irradiation with uniform light color and high brightness.

Toughened glass surface, with high hardness, not easy to break.

It comes with different CCT, RGB LED sources and C5 Marine Grade Coating, this family is a perfect solution to the requirement.

The length can be customized 250mm, 500mm, 750mm, 1.5mtr.

Control Mode : DMX512

They are commonly used in architectural lighting to enhance the aesthetics of buildings, highlight textures, and create visually appealing lighting effects.

### Product Specifications:

Housing : Die cast Aluminum

Glass : Tempered glass

Gasket: Molding shaped silicone seal

Accessory: Side cover

Lens/Reflector : Optical lens (efficiency>90%)

Power Cable: 0.5 mt. power cable included

Driver : High efficiency, low flicker driver

Installation Type: Surface Mounted

### Technical Specifications:

Wattage: 18W

Voltage: AC85V-265V / DC24V

Frequency: 50-60Hz

Light Source: OSRAM/EPISTAR/CREE

Lumen: 120lm/W

Mac Adam: 3 Step

Safety Class: I

Working Temperature: -25°C to 60°C

Life Time: 50,000hrs (L80/B10) at 35°C

Humidity : <95%

Warranty: 5 Years

### Parameter:

Wattage(W) : 18W

Finish : Grey (G)

Kelvin\* : 2700K/ 3000K/ 4000K/ 6000K/ RGB / RGBW

Beam Angle : 30°/ 45°/ 60°/ 15°x 45°/ 10°x 60°


CRI : 80+

Control Mode : ON/OFF / DALI / 0 / 1-10V / Phase Cut / DMX

### Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
5493060	18 - 18W	27-2700K	D-24VDC	30-30°	G - Grey	1-ON/OFF
		30-3000K		45-45°		2-DALI
		40-4000K		60-60°		3-0/1-10V
		60-6000K		15x45-15°x45°		4-Phase cut
		92-RGB		10x60-10°x60°		5-DMX
		93-RGB DMX				
		82-RGBW				

### Photometric:



### Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C

Ex: Order Code: 54930601827D'30G1

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode	
5493060	18 - 18W	27-2700K	A - 85V-265VAC	30-30°	SS-Stainless Steel 304	1-ON/OFF	
		30-3000K		45-45°		2-DALI	
		40-4000K		60-60°		3-0/1-10V	
		60-6000K		15x45-15°x45°			
				10x60-10°x60°			

54930601827A'30SS

Ex: Order Code: 1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at  $\pm 5\%$ . Unless stated otherwise, the values apply to an ambient temperature of 25°C