


RERO



Description:

RERO is a modern Bollard Light combines functionality with architectural elegance. Each Head can be rotated at 360°, light engine adjusted to 45°, allowing flexible directional lighting tailored to specific site requirements.

The fixture is constructed from durable extruded aluminum housing, offering excellent corrosion resistance and long-lasting performance. With THD less than 10% and a power factor greater than 0.9, it ensures high electrical efficiency and superior performance.

Available with Inventronic Driver.

Available in a range of refined RAL finishes including Black (RAL 9011), Concrete Grey (RAL 7023), Metallic Grey (RAL 7011), and Grey (RAL 9023) to complement a variety of urban design aesthetics. C5 Marine Grading Available on Request.

A perfect solution for projects that demand versatility, reliability, and modern appeal in outdoor lighting.

Product Specifications:

- Housing : Die cast Aluminium
- Diffuser : Polycarbonate
- Coating: Powder Coating
- Gasket: Moulding shaped silicone seal
- Power Cable: 0.5 mtr. power cable included
- Driver : High efficiency, low flicker driver
- Installation Type: Surface Mounted
- Adjustable: Yes
- Warranty: 5 Years

Technical Specifications:

- Wattage: 2*15W
- Voltage: 220-240V AC
- Frequency: 50-60Hz
- Power Factor : 96%
- Coefficient cosφ : >0.9
- Light Source: CREE / LumiLEDs
- Lumen: 90lm/W
- Mac Adam: 3 Step
- Safety Class: II
- Working Temperature:-30°C to 50°C
- Life Time: 50,000hrs (L70/B50) at 40°C

Parameter:


Wattage(W)	: 2*15W
Finish	: RAL 9011 (B) / RAL 7023 (CG) / RAL 7011 (MG) / RAL 9023 (G)
Kelvin*	: 2700K/ 3000K / 4000K
Optics	: 51° (Wide)
CRI	: 90+
Control Mode	: ON/OFF / DALI

Order Code:

Product Code	Wattage	CCT	Voltage(AC)	Optics	Finish	Control Mode
547120	2*15 - 2*15W	27-2700K	A - 220-240VAC	51 - 51°	B-RAL 9011	1-ON/OFF
		30-3000K			CG-RAL 7023	2-DALI
		40-4000K			MG-RAL 7011	
					G-RAL 9023	

Ex: Order Code: 5471202*1527A'51B1

Photometric :



Standards :

- EN 60598-1
- EN 60598-2-2
- EN 60598-3-2
- EN 60598-3-3

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at ±5%. Unless stated otherwise, the values apply to an ambient temperature of 25°C