


RETRO



Description:

RETRO is wall light features a die-cast lamp body with electrostatic plastic coating. Lamshade adopts high strength toughed glass, resist the impact and friction, has excellent rain water clean ability. Adopt double waterproof structure and easy installation ways meet the various occasions demands for outdoors projects.

Product Specifications:

Housing : Die cast Aluminium
Diffuser : Tempered glass.
Gasket: Moulding shaped silicone seal
Lens/Reflector : Optical lens (efficiency>90%)
Power Cable: 0.5 mt. power cable included
Driver : High efficiency, low flicker driver
Installation Type: Surface mounted
Adjustable: No
Warranty: 5 Years


Technical Specifications:

Wattage: 4 - 8W
Voltage: 24VDC / 220-240VAC
Frequency: 50-60Hz
Light Source: OSRAM/EPISTAR/CREE
Lumen: 100lm/W
Mac Adam: 3 Step
Safety Class: II
Working Temperature:-20°C to 55°C
Life Time: 50,000hrs (L80/B10) at 35°C

Parameter:

Wattage(W)	:	4W / 8W
Finish	:	Black (B) / Grey (SG)
Kelvin*	:	2700K/ 3000K / 4000K / 6000K / RGB / RGB DMX
Beam Angle	:	2° / 20° / 30° / 60°
CRI	:	80+
Control Mode	:	ON/OFF / DALI / 0 / 1-10V

Photometric:



Order Code:

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540129	4 - 4W	27-2700K	D-24VDC	2 - 2°	B-Black	1-ON/OFF
	8 - 8W	30-3000K		20 - 20°	G - Grey	2-DALI
		40-4000K		30 - 30°		3-0/1-10V
		60-6000K		60 - 60°		

Ex: Order Code: 540129427D'2B1

Standards :

EN 60598-1

EN 60598-2-2

EN 60598-3-2

EN 60598-3-3

Product Code	Wattage	CCT	Voltage	Beam Angle	Finish	Control Mode
540129	4 - 4W	27-2700K	A - 100 - 240VAC	2 - 2°	B-Black	1-ON/OFF
	8 - 8W	30-3000K		20 - 20°	G - Grey	2-DALI
		40-4000K		30 - 30°		3-0/1-10V
		60-6000K		60 - 60°		

Ex: Order Code: 540129427A'2B1

Pluxb luminaires are developed with globally recognized and tested components suppliers, however as per international standards tolerance in initial flux and connected load is at $\pm 5\%$. Unless stated otherwise, the values apply to an ambient temperature of 25°C